

Reduce Grain Drying Costs for next Fall
Scott Sanford
Senior Outreach Specialist
Wisconsin Focus on Energy / Rural Energy Issues
University of Wisconsin, Biological Systems Engineering

Natural gas and propane prices have been increasing over the past few years due to increasing demand and the continued instability in oil producing areas of the world. In October 2004 natural gas prices climbed to an all time high of \$9.00 per mmBtu on the NYMEX commodity exchange for natural gas delivered to the Henry Hub in Louisiana before retreating to the \$7.00 range in December 2004. Prices for 2004 were 149% higher than 5 years ago and 80% higher than 2 years ago. The Future prices for 2005 are trending down from current levels to \$6.40 to \$6.50 per mmBtu until November 2005 when prices are forecasted to rise to about \$7.30 for the 2005-2006 heating season. Propane prices have also taken a dramatic jump with wholesale prices reaching record levels at \$0.97 per gallon in October 2004, 64% above October 2003 prices and 115% higher than the average price for October 1999, five years earlier. Natural gas or propane is a major cost of high temperature grain drying. The long-term natural gas price forecast predicts prices to decline only about 5% as new wells come on line. Current propane prices for 2005 to 2007 are forecasted to be 15% above the 2004 price levels. Political instability and high demand will continue to affect future prices for both natural gas and propane.

More information on what drives propane prices can be found at
http://tonto.eia.doe.gov/FTP/ROOT/other/Propane_Prices_Pub.pdf.

Estimating fuel costs:

One can estimate the energy costs for high temperature drying at 0.02 gallons per bushel per percentage point of moisture removed for propane or 0.018 therms of natural gas per bushel per percentage point of moisture removed.

Example: 50,000 bushels dried from 23% to 17% moisture could be calculated as:
 $50,000 \times 6\% \text{ moisture} \times 0.02 = 6000 \text{ gallons propane}$

The following are some things that can be done to reduce the impact of higher energy costs.

Can the grain be used as “High Moisture Shelled Corn” (HMSC) instead of dried shell corn?

This avoids the cost of drying. If storage is not available, there will be some cost for temporary storage but is usually less than the energy cost to dry the corn. A sealed silo is optimal for storage of HMS corn but an open silo or a silo bag can also be used provided the grain can be fed out fast enough to prevent spoilage and lower feed quality. Regardless of storage type, the HMS corn should be harvested at 25 to 30% moisture to get good fermentation. This could also aid in spreading out the harvesting time frame, allowing corn to be harvested earlier than corn that will be dried. If temporary storage such as a silo bag is used, care must be taken to make sure the bag is air tight and any holes are patched to minimize spoilage. Putting up enough HMS corn to provide feed for the cold months, November to March, will save a considerable amount of energy and have the lowest risk for spoilage. More information on storing shelled corn in silage bags can be found at
www.bae.umn.edu/extens/ennotes/enspr01/storage.htm.

Delay harvest of corn to allow field dry down.

This is usually a trade off between increased field losses, time available for harvest, drying capacity and weather affecting the ability to harvest the crop. Delaying harvest early in the season usually has favorable results, but later in the fall the field loss will likely be greater than energy cost savings. Choosing varieties that mature earlier in the fall will allow more time for natural field drying without increased field losses associated with late harvests.

Tune up your drying system.

Clean screens and aeration floors, check belt drives (make sure safety guards are in place), clean fan housing and blades, calibrate temperature sensing devices, clean and check burner for proper operation, have gas company personnel check gas pressure regulators and have any grain moisture tester or sensors calibrated annually. Here is two link to a fact sheets to ensure dryers are operating efficiency: the first is entitled “Last Minute Grain Dryer Checks” - www.ces.purdue.edu/extmedia/GQ/GQ-19.html and the second is titled “Optimizing Grain Dryer Operations” - www.ces.purdue.edu/extmedia/GQ/GQ-15.htm .

Reduce over-drying.

Corn can be safely stored at 14-15% moisture for 6 to 9 months. If grain is over-dried, there is less to sell and it is more susceptible to cracking and breakage. Besides using more energy, over-drying also reduces dryer capacity.

Clean grain before it enters the dryer to remove fines.

Cleaning grain to remove fines will ensure unrestricted flow of air through the column or pile of grain which will increase dryer efficiency and saves energy (energy not used to dry fines). If filling a bin where the grain will be dried and stored, a distribution spreader is recommended to achieve level fill and to evenly distribute any remaining fines. Clean grain in bin dryers will reduce the risk of spoilage by reducing areas that have poor air flow due to the accumulation of fines. The results of a study that looked at the affects of cleaning grain can be found at www.extension.umn.edu/extensionnews/2003/NewUofMstudy.html.

Do you have a grain bins with a full perforated floors and aeration?*Option 1 - Low temperature bin drying*

You might consider using ambient or natural air drying if the corn crop comes out of the field at less than 22% moisture. Ambient or low temperature bin drying in a typical weather year uses *half the energy* that a typical cross-flow high temperature dryer uses. The energy source switches from 98% natural gas or propane to 100% electrical energy. You will need a minimum of 1.25 cfm per bushel air flow rates for Wisconsin. The fan requirement works out to $\frac{3}{4}$ to 1 horsepower per 1000 bushels of corn for grain up to 18 ft deep. If multiple grain bins are available, fill them each with a layer of grain (layered fill) rather than filling one bin at a time. This allows the grain to dry faster because of higher air flow due to less grain depths (higher air flow rate per bushel) and reduces the risk of spoilage. Fans are started when the filling starts and run constantly until the grain is dry, usually 4 to 8 weeks or until the grain temperature drops below 30°F. If the grain is not completely dried before winter, it will be necessary to finish drying in the spring when the temperature rises above freezing. Refer to MidWest Plan Service publication MWPS-22, "Low Temperature & Solar Grain Drying Handbook" for additional information or an on-line source is available at www.extension.umn.edu/distribution/cropsystems/DC6577.html

Option 2 - Using Combination drying

To reduce some of the risks with ambient air drying, use a high temperature dryer to dry the corn down to about 20% and then finish drying it using ambient air or a low temperature bin dryer. The grain can be transferred hot to the bin dryer and the aeration fans are started immediately. This can reduce energy requirements by up to 60% and will improve grain quality due to less kernel cracking. The capacity of a high temperature dryer is doubled or tripled using combination drying.

If you are using a cooling section on your continuous flow dryer, does it have heat recovery?

Adding heat recovery to your existing dryer to recycle air can save 10-15% in energy usage. Recycling the cooling air for some of the intake air to the heating section of the dryer by reverse flow through the grain or by ducting the exhaust from the cooling section to the inlet of the heating section can save 10-15% in heating costs. If heat recovery is added to the lower heating column, an additional 5-10% in heating costs can be saved. Heat recovery can also be added to the lower section of full heat dryers for a 5-10% energy savings.

Want more dryer capacity, better grain quality and save energy?

Using In-bin cooling or Dryeration will reduce energy use by 15 to 25%, respectively, while increasing dryer through put by 33 to 70%, respectively. The dryer is operated in a full heat mode for either process. With In-bin cooling the grain is removed from the dryer while still hot, transferred to a storage bin and cooled. The grain exiting the dryer can be about 1-1.5% moisture above the desired storage moisture percentage. The moisture is removed during the slow cooling process in the storage bin. With Dryeration the grain can exit the dryer about 2-3% moisture above the desired storage moisture percentage. The grain is transferred hot to an intermediate holding bin where the grain is allowed to steep for 4 to 12 hours before the cooling fans are started. This process allows the kernel moisture to equalize which results in less kernel stress and cracking. Typically two intermediate holding bins will be needed for this process. The grain should be removed from the steeping bin to eliminate spoilage from condensation on the bin walls. A Dryeration cycle typically requires 48 hours to fill,

steep, cool and empty a bin. Refer to Midwest Plan Service publication MWPS-13, "Grain Drying, Handling and Storage Handbook", for additional information or on-line information is available at www3.extension.umn.edu/distribution/cropsystems/DC7356.html.

Adding a stirring device to your bin dryers can save 20 to 30% in drying costs.

A stirring device will loosen the grain and increase air flow through the mass, resulting in an increased drying rate. It also mixes dry grain from the bin floor with higher moisture grain from the upper layers, reducing over drying. Studies suggest stirring the grain two or three times: the first time right after filling the bin, a second time when the grain is about half dry (about 20%) if the initial grain moisture was greater than 22%, and the third time when the average grain moisture is 15.5% moisture is sufficient. Over stirring can lead to fines sifting to the drying floor which reduces air flow.

Need to replace a grain dryer? Choose a high efficiency type.

Aside from natural air bin dryers, continuous flow In-bin dryers are the most efficient high temperature dryers using only 60% of the energy that a typical continuous cross-flow dryer would use. Often an existing storage bin can be retrofitted to be used as a bin dryer which reduces initial costs, and the bin/dryer can still be used to store the last batch of grain of the season by drying it in a recirculating bin dryer mode. Another type of high efficiency continuous flow dryer is a mixed-flow column dryer. The air flow through the grain is both in a concurrent and counter flow path which is why it is called a mixed flow dryer. Due to the relatively short air path and multiple plenum zones, dryers can be adjusted to optimize crop drying needs. These dryers can be used to dry all sizes of seeds and don't have screens that need to be cleaned daily.

Do you use a low temperature dryer? Add solar heating.

Solar assisted heating has been shown to reduce drying time and energy costs between 9% and 13% in an Iowa study. Intake air was drawn through a solar collector before it entered the grain bin. The solar collector increased the air temperature in this study an average of 2.1°F. The amount of saving provided by solar heating will vary with weather and collector area. Refer to Midwest Plan Service publication MWPS-22, "Low Temperature & Solar Grain Drying Handbook", for additional information.

Do the controls on your dryer give you consistent drying?

Updating the controller on your current dryer can increase its efficiency. Two-stage burners and modulated burners can reduce the extreme temperature variation caused by on / off thermostatic controls for high temperature dryers. Moisture and temperature sensors in the grain can be used to sense when the grain is dry enough to remove from the dryer, preventing over-drying and reducing energy costs. A humidistat can be used in a low temperature dryer to control a heater to keep the humidity below a specified level for faster drying.

Energy Efficiency Grants:

Wisconsin has a grant program, Focus on Energy, to aid growers in becoming more energy efficient. The grants can be used to cover up to 25% of the cost of equipment and are based on the estimated first year energy savings. Growers must be in a participating utility's service area. For more information, call 1-800-762-7077 or access the web site at www.focusonenergy.com.

The 2002 Farm Bill also provides funds for renewable energy and energy efficiency projects. The Notice of Funding is usually published in May each year with applications due in mid-July. Grants cannot exceed 25% of total project costs and range from a minimum of \$2500 to \$500,000. Energy efficiency projects must demonstrate at least a 15% energy savings and an 11-year investment payback to be considered. Application are handled by the USDA Rural Development office in each state. The Wisconsin office is located in Stevens Point and can be contacted at 715-345-7615. More information and applications can be found at www.elpc.org/farmenergy/9006FAQ.htm or www.rurdev.usda.gov/rbs/farbill/index.html.

Online Resources:

Purdue University maintains a website with all known grain drying related information on the web. - <http://pasture.ecn.purdue.edu/~grainlab/exten-pubs.htm>

University of Minnesota – Grain Drying, Handling and Storage website -

<http://www.extension.umn.edu/topics.html?topic=4&subtopic=44>

Saving Fuel in Corn Drying, Bill Wilcke, www.bae.umn.edu/extens/enotes/enaug01/corndrying.htm

References:

Low Temperature & Solar Grain Drying Handbook, MWPS-22, Midwest Plan Service, Ames, IA, 1980.

Grain Drying, Handling and Storage Handbook, MWPS-13, Midwest Plan Service, Ames, IA, 1987.

Dry Grain Aeration Systems Design Handbook, MWPS-29, Midwest Plan Service, Ames, IA, 1997.

Wilcke, W.F., C.J. Bern, "Natural-Air Corn Drying with Stirring: II. Dryer Performance", ASAE Transactions Vol. 29, no. 3, pg 860-867, 1986.

Midwest Plan Service publications can be order online from Midwest Plan Service at www.mwpsHQ.org or contact them at 1-800-562-3618 or mwps@iastate.edu.

